



Safety Data Sheet

Product : Acetylene (dissolved)

Page :1/5

MSDS Nr : 001_AL

Version : 1.01

Date : 31/07/2002

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MSDS Nr	001_AL
Product name	Acetylene (dissolved)
Chemical formula	C2H2
Company identification	see heading and/or footer see paragraph 16 "OTHER INFORMATION"
Emergency phone numbers	see heading and/or footer see paragraph 16 "OTHER INFORMATION"

2 COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation	Substance.
Components/Impurities	Contains no other components or impurities which will influence the classification of the product.
CAS Nr	00074-86-2
EEC Nr (from EINECS)	200-816-9

3 HAZARDS IDENTIFICATION

Hazards identification	Dissolved gas Extremely flammable
------------------------	--------------------------------------

4 FIRST AID MEASURES

Inhalation	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Ingestion	Ingestion is not considered a potential route of exposure.

5 FIRE FIGHTING MEASURES

Specific hazards	Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products	Incomplete combustion may form carbon monoxide.
Suitable extinguishing media	All known extinguishants can be used.
Specific methods	If possible, stop flow of product. Move away from the container and cool with water from a protected position.

Safety Data Sheet

Product :

Acetylene (dissolved)

Page :2/5

MSDS Nr : 001_AL

Version : 1.01

Date : 31/07/2002

Continue water spray from protected position until container stays cool.
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.
In confined space use self-contained breathing apparatus.

Special protective equipment for fire fighters

6 ACCIDENTAL RELEASE MEASURES

Personal precautions	Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Evacuate area. Ensure adequate air ventilation. Eliminate ignition sources.
Environmental precautions	Try to stop release.
Clean up methods	Ventilate area.

7 HANDLING AND STORAGE

Handling and storage	Ensure equipment is adequately earthed. Avoid contact with pure copper, mercury, silver and brass with greater than 70% copper. Suck back of water into the container must be prevented. Purge air from system before introducing gas. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Keep away from ignition sources (including static discharges). Segregate from oxidant gases and other oxidants in store. Refer to supplier's container handling instructions. Keep container below 50°C in a well ventilated place.
----------------------	---

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection	Ensure adequate ventilation. Wear suitable hand, body and head protection. Wear goggles with suitable filter lenses when use is cutting/welding. Do not smoke while handling product.
---------------------	---

9 PHYSICAL AND CHEMICAL PROPERTIES

Molecular weight	26
Melting point	-80.8 °C

Safety Data Sheet

Product :

Acetylene (dissolved)

Page :3/5

MSDS Nr : 001_AL

Version : 1.01

Date : 31/07/2002

Boiling point	-84(s) °C
Critical temperature	35 °C
Relative density, gas	0.9 (air=1)
Relative density, liquid	Not applicable.
Vapour Pressure 20°C	44 bar
Solubility mg/l water	1185 mg/l
Appearance/Colour	Colourless gas
Odour	Garlic like
	Poor warning properties at low concentrations.
Autoignition temperature	325 °C
Flammability range	2.4-83 vol% in air.

10 STABILITY AND REACTIVITY

Stability and reactivity	Can form explosive mixture with air. May decompose violently at high temperature and/or pressure or in the presence of a catalyst Forms explosive acetylides with copper, silver and mercury. Do not use alloys containing more than 70% copper. Dissolved in a solvent supported in a porous mass. May react violently with oxidants.
--------------------------	---

11 TOXICOLOGICAL INFORMATION

General	No known toxicological effects from this product.
---------	---

12 ECOLOGICAL INFORMATION

General	No known ecological damage caused by this product.
---------	--

13 DISPOSAL CONSIDERATIONS

General	Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required.
---------	--

14 TRANSPORT INFORMATION

Proper shipping name	Acetylene, dissolved
UN Nr	1001
Class/Div	2.1

Safety Data Sheet

Product :

Acetylene (dissolved)

Page :4/5

MSDS Nr : 001_AL

Version : 1.01

Date : 31/07/2002

ADR/RID Classification code	2, 4°F
ADR/RID Hazard Nr	230
Labelling ADR	Label 3: flammable gas
Other transport information	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured and: - cylinder valve is closed and not leaking - valve outlet cap nut or plug (where provided) is correctly fitted - valve protection device (where provided) is correctly fitted - there is adequate ventilation. - compliance with applicable regulations.

15 REGULATORY INFORMATION

Number in Annex I of Dir 67/548	601-015-00-0.
EC Classification	R5[R6]F+;R12
-Symbols	F+: Extremely flammable
-Risk phrases	R5 Heating may cause an explosion. R6 Explosive with or without contact with air. R12 Extremely flammable.
-Safety phrases	S9 Keep container in well ventilated place. S16 Keep away from ignition sources - No smoking. S33 Take precautionary measures against static discharges.

16 OTHER INFORMATION

Ensure all national/local regulations are observed.

Ensure operators understand the flammability hazard.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

Safety Data Sheet

Product :

Acetylene (dissolved)

Page :5/5

MSDS Nr : 001_AL

Version : 1.01

Date : 31/07/2002

This MSDS is for information purposes only and is subject to change without notice. [Prior to purchase of products, please contact your local Air Liquide office for a complete MSDS (with Manufacturer's name and emergency phone number).]

End of document.

Number of pages :5