

MATERIAL SAFETY DATA SHEET

ISSUE NO. : 3

ISSUE DATE: 2nd July 2002

PAGE: 1 OF 5

IDENTIFICATION

HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

PRODUCT NAME: PIPE GRIP SOLVENT CEMENT TYPE N

Manufacturers Code: Not established

U.N. Number:	1133
Dangerous Goods Class:	Flammable Liquid/3
Subsidiary Risk:	Nil
Hazchem Code:	3[Y]E
Poisons Schedule Number:	N/A
Dot Hazard Classification:	Flammable Liquid
Packaging Group:	II
EPG:	3A1

USE: ADHESIVE/SOLVENT CEMENT FOR PVC PIPES.

PHYSICAL DESCRIPTION/PROPERTIES

Appearance:	Clear midnight blue viscous liquid
Specific Gravity:	0.88 - 0.90
Evap. Rate:	Not applicable
Boiling Point/Range (°C):	79.6°C
Percent Volatile:	>80
Flash Point:	-9°C
Solubility In Water:	Not Miscible
pH @ 20°C:	Not available
Viscosity (cps @ 20°C):	340-450

INGREDIENTS

CHEMICAL ENTITY	CAS NO.	PROPORTION %w/w
Methyl Ethyl Ketone	79-93-3	60 - 80
Cyclohexanone	108-94-1	10 - 20
Other ingredients which are classified as not hazardous		to 100%

HEALTH HAZARD INFORMATION

HEALTH HAZARDS

Inhaled: Will cause irritation to mucous membranes, nose, eyes, throat and coughing, difficulty in breathing. Exposure to high vapor concentrations may cause headaches, dizziness, nausea and narcosis.

Eye: May irritate or burn eyes.

Skin: Prolonged or repeated contact with the skin may irritate and cause dermatitis.

Swallowed: Harmful if swallowed, may cause gastric irritation and narcosis. The hazard of solvent aspiration into the lungs may cause mild to severe pulmonary injury and possible death.

FIRST AID

Inhaled: Remove victim to fresh air, if not breathing employ artificial respiration preferably mouth to mouth. If breathing is difficult give oxygen and seek medical advice.

Eye: Immediately irrigate with copious quantities of water, for at least 20 minutes, holding the eyelids open. In all cases of eye contamination, it is advisable to medical advice.

Skin: Remove contaminated clothing including footwear. Wash affected areas with soap and water immediately.

Swallowed: If poisoning occurs contact a doctor or Poisons Information Center. If swallowed, and more than 15 minutes from a hospital induce vomiting, preferably using Ipecac Syrup APF. If vomiting occurs, place victim's face downwards, head lower than hips to prevent vomit entering lungs. Seek immediate medical assistance.

Advice to Doctor: Vapors can cause moderate irritation of the eyes or respiratory system. Effect is temporary.

PRECAUTIONS FOR USE

This product is stable and hazardous polymerization will not occur.

THERMAL DECOMPOSITION/HAZARDOUS DECOMPOSITION PRODUCTS

Irritating fumes emitted.

CONDITIONS TO AVOID INSTABILITY:

Material is stable in closed container with oxygen and light excluded. Inside storage should be in a standard flammable liquids storage room or cabinet. Possible formation of peroxides may cause violent reaction especially upon evaporation to dryness. Unstable peroxide may form upon aging, especially in contact with air. Test for peroxides prior to distillation.

CONDITIONS TO AVOID HAZARDOUS DECOMPOSITION:

Not applicable

MATERIALS & CONDITIONS TO AVOID INCOMPATIBILITY:

Oxidizing materials, air (if unstable), Lithium aluminium hydride, sodium aluminum hydroxide, sodium hydroxide, potassium hydroxide.

EXPOSURE LIMITS:

Not established for product. See page 2 for exposure limit for individual raw material.

PERSONAL PROTECTION:

Wear chemically resistant gloves, chemical splash goggles. Use approved respiratory protection such as air supplied mask if used in enclosed area.

VENTILATION:

Use adequate ventilation.

SAFE HANDLING

STORAGE AND TRANSPORT:

Storage: Material is dangerous when exposed to heat or flame. Keep container closed when not in use. Do not handle or store near open flame, heat or strong oxidants, adequate ventilation required.

DOMESTIC DATA:

DOT SHIPPING NAME: Adhesives containing flammable liquid (Contains Cyclohexanone and Methyl Ethyl Ketone)
DOT HAZARD CLASS: Flammable liquid/3

EXPORT DATA

EXPORT SHIPPING NAME: Adhesives containing flammable liquid (Contains Cyclohexanone and Methyl Ethyl Ketone)
EXPORT HAZARD CLASS: Flammable Liquid /3

SPILLS AND DISPOSAL

Small Spills: Absorb in sand or other non-combustible material. Place in clean drum then flush area with water.

Large Spills: Keep public away, shut off all source of ignition. Warn occupants of down-wind areas of explosion hazard. Wear self-contained breathing apparatus, rubber boots and heavy rubber gloves. Ventilate area and wash spill site after material pickup is complete. Absorb on sand or vermiculite and place in closed container for disposal. Prevent liquid from entering sewers, watercourse or low areas.

WASTE DISPOSAL METHOD

Contain spilled liquid with sand or earth. Dilute contained spill with water. Recover free liquid by pumping onto a suitable absorbent. Consult an expert on disposal of recovered material and ensure conformity to local regulations.

FIRE/EXPLOSION HAZARD

Flash point: -9°C
Method: Abel close cup
Flammable Limits: LEL: 1.8 UEL: 10.0
Autoignition Temperature: 515°C

GENERAL HAZARD

Vapor may travel a considerable distance to source ignition and flashback possible formation of peroxide may cause violent reaction especially upon evaporation to dryness.

FIRE FIGHTING PROCEDURES:

Wear self contained breathing apparatus and chemical goggles.

HAZARDOUS DECOMPOSITION PRODUCT UNDER FIRE CONDITIONS:

Irritating fumes emitted when heated to decomposition.

FIRE FIGHTING MEDIA:

Foam, dry chemical, carbon dioxide, Water spray may be ineffective.

OTHER INFORMATION


CONTACT POINTS

POISONS INFORMATION CENTRE: 131126 (from anywhere in Australia)

POLICE OR FIRE BRIGADE: 000 **EXCHANGE:** 132203

Name: Lester Jones

Title: Operations Manager

Signature: 

Tel. No.: (02) 9681 3666

Although the information and recommendations provided in this MSDS are presented in good faith and are believed to summarise our best knowledge of the health and safety information for the product, Atherton Chemicals makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving the product will make their own determination as to its suitability for their use and make appropriate risk assessments prior to use. In no event will Atherton Chemicals be responsible for damage of any nature whatsoever resulting from the use or reliance upon information. No representations or warranties, either expressed or implied, as to merchantability, fitness for a particular, or any other, purpose are made with respect to the information or to the product to which information refers.