

1. COMPANY DETAILS

MANUFACTURER'S NAME: DENSO (AUSTRALIA) PTY LTD
REGULAR TELEPHONE NUMBER: 03 9356 7600
EMERGENCY TELEPHONE NUMBER: 03 9356 7600
FACSIMILE NUMBER: 03 9387 6973

ADDRESS: 411-413 Victoria Street
BRUNSWICK VICTORIA 3056

PRODUCT NAME :

DENSO MP PRIMER, DENSO VAPOURSEAL PRIMER, MANHOLE SEALING GREASE, DENSO VOID FILLER, DENSO TAPE, DENSYL TAPE, DENSO MASTIC, DENSYL MASTIC, HI TACK TAPE, *TERMITESHIELD TAPE, DENSO VN TAPE, *DENSO HOTLINE TAPE, DENSYL SUPERSOFT MASTIC, DENSO COLOURTAPE

2. IDENTIFICATION

UN No.: None Allocated
DG Class: None Allocated
Packing Group: None Allocated
Hazchem Code: None Allocated
Poisons Code: Not Scheduled

3. HAZARDOUS INGREDIENTS

MATERIAL OR COMPONENT:	Nil	} None of the ingredients are hazardous, according to Criteria of Worksafe Australia.
PERCENTAGE:	Nil	
HAZARD DATA:	Nil	

3a. NON HAZARDOUS INGREDIENTS (According to Criteria of Worksafe Australia)

REFINED MINERAL OIL: Complex mixture of Paraffinic, Napthenic & Aromatic Hydrocarbons (CAS mixed) 20%

Paraffin Wax (CAS not required) 70%

Mineral Talc (CAS not required) 10%

*PVC FILM

*APPLIES TO:
TERMITESHIELD TAPE
VN TAPE
DENSO HT TAPE**4. PHYSICAL DATA**

BOILING POINT 760MM HG:	1 BP / Not available - FBP / Not available
SPECIFIC GRAVITY [H ₂ O.1]:	1.2
VAPOUR DENSITY [AIR.1]:	N/A
% VOLATILES BY VOLUME:	<1
APPEARANCE AND ODOUR:	Brown waxy adhesive.
MELTING POINT:	65°C
VAPOUR PRESSURE:	N/A
SOLUBILITY IN H ₂ O[% BY WT]:	<1
EVAPORATION RATE [BUTYL ACETATE.1]:	N/A

5. FIRE AND EXPLOSION DATA

FLASH POINT [TEST METHOD]:	CC480°C
AUTO IGNITION TEMPERATURE:	<500°F

FLAMMABLE LIMITS IN AIR % BY VOLUME:

LOWER: N/A

UPPER: N/A

EXTINGUISHING MEDIA: Carbon dioxide, dry powder, chemical foam, water fog

SPECIAL FIRE FIGHTING PROCEDURES: None known

UNUSUAL FIRE AND EXPLOSION HAZARD: None known

6. HEALTH HAZARD INFORMATION

HEALTH HAZARD DATA:

ROUTES OF EXPOSURE:-

INHALATION:	N/A
SKIN CONTACT:	May cause irritation
SKIN ABSORPTION:	N/A
EYE CONTACT:	May cause irritation
INGESTION:	Not toxic

EFFECTS OF OVER-EXPOSURE:

ACUTE OVEREXPOSURE: N/A

CHRONIC OVER-EXPOSURE: N/A

EMERGENCY AND FIRST AID PROCEDURES:

EYES:	Irrigate thoroughly with water
SKIN:	Wash thoroughly with soap and water
INHALATION:	N/A
INGESTION:	Do not induce vomiting

NOTES TO PHYSICIAN: None

7. REACTIVITY DATA

CONDITIONS CONTRIBUTING TO INSTABILITY: None known

INCOMPATIBILITY: With aromatic solvents, not suitable for use in potable water

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, water, oil, fume & Hydrogen Chloride Gas from *PVC Backing (*Applies to Termiteshield Tape, VN Tape, Denso HT Tape)

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: None known

8. SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: N/A

NEUTRALIZING CHEMICALS: None

WASTE DISPOSAL METHOD: Incineration or approved dumping

9. SPECIAL PROTECTION INFORMATION

VENTILATION REQUIREMENTS: No special requirements

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT: None

RESPIRATORY [SPECIFY IN DETAIL]: N/A

EYE: None

GLOVES: Grease resistant

OTHER CLOTHING AND EQUIPMENT: N/A

10. SPECIAL PRECAUTIONS

PRECAUTIONARY STATEMENTS: Contains petroleum products, which may affect the skin.

USERS ARE RECOMMENDED TO: Wash thoroughly after use and before work breaks to remove compound from the skin.

Do not use paraffin or other solvents to clean the skin. Change clothing when soiled.

OTHER HANDLING AND STORAGE REQUIREMENT: Store in a cool place away from boilers or heaters in original packing.

PREPARED BY: Denso (Australia) Pty Ltd

ADDRESS: 411-413 Victoria Street
BRUNSWICK VICTORIA 3056

DATE: December 12, 2002