

MATERIAL SAFETY DATA SHEET FOR: EASY SEAL PAINT IT SILICONE

Replaces: May 2001. Date of issue: May 2003

COMPANY DETAILS

Company: H. B. Fuller Company
Address: 16-22 Red Gum Drive, Dandenong South VIC 3175
Telephone: (03) 9797 6222
Emergency Telephone No: 1800 033 111

Not classified as hazardous according to criteria of Worksafe Australia

IDENTIFICATION

Product Name: Easy Paint It.
Other Names: None
Manufacturer's Code: Not applicable
UN Number: None assigned
Dangerous Goods Class: None assigned
Subsidiary Risk: None assigned
Hazchem Code: Not assigned
Poisons Schedule: Not scheduled
Packaging Group: Not assigned
Use: Sealant in glazing applications where painting of the sealant is required. Apply directly from cartridge using a caulking gun.

Physical Description/Properties

Appearance: White, viscous paste
Melting Point: Not established
Boiling Point: Not relevant
Vapour Pressure: Not established
Specific Gravity: 1.35
Flashpoint: Not applicable
Flammability Limits: Not established
Solubility in water: Partially soluble if uncured

Other Properties

Will cure on contact with water or water vapour.

Ingredients

CHEMICAL ENTITY	CAS NO	PROPORTION
Dimethyl siloxane, hydroxy-terminated	70131-67-8	High
Limesone	1317-65-3	High
Water	7732-18-5	Med.
Polyethylene glycol nonylphenol	9016-45-9	Low
Other ingredients determined not to be hazardous	Not applicable	Low

Low <10% Med. 10-30% High 30-60% V High >60%

MATERIAL SAFETY DATA SHEET FOR: EASY SEAL PAINT IT SILICONE

Replaces: May 2001. Date of issue: May 2003

HEALTH HAZARD INFORMATION**Health Effects***ACUTE:*

Swallowed:

Small amounts transferred to the mouth by fingers during use, are unlikely to injure. swallowing large amounts may cause stomach discomfort.

Eye:

Direct contact may cause moderate irritation with redness and swelling.

Skin:

Contact with skin may result in irritation.

Inhaled:

Slight irritant to respiratory system.

CHRONIC:

Prolonged or repeated contact may result in skin sensitisation due to presence of small amounts of diethylamine.

First Aid

Swallowed:

If swallowed, rinse mouth thoroughly with water. Seek medical advice.

Eyes:

If in eye, irrigate immediately with copious amounts of water for 15 minutes with eyelids held open.

See a doctor.

Skin:

Wash affected areas immediately with copious quantities of soap and water.

Remove contaminated clothing and wash before reuse. See a doctor if irritation persists.

Inhaled:

If ill effects persist, seek medical advice.

First Aid Facilities:

Have eyewashes available where contact with eye can occur.

Advice to Doctor

Treat symptomatically.

MATERIAL SAFETY DATA SHEET FOR: EASY SEAL PAINT IT SILICONE

Replaces: May 2001. Date of issue: May 2003

PRECAUTIONS FOR USE

Exposure Standards [NOHSC: 1003 (1995)]:

Limestone (Inspirable dust):
Polyethylene glycol**TWA.**10 mg/
10 mg/m³

Engineering Controls:

If not working in open air use good general ventilation that will ensure that atmospheric exposure standards are not exceeded. In confined spaces, use a local exhaust that will give sufficient face velocity away from the user to ensure that the exposure limits are not exceeded.

Personal Protection:

Wear safety overalls, safety glasses and rubber gloves. Avoid contact with skin and eyes. Avoid breathing vapour. Always wash hands before smoking, eating, drinking or using the toilet.

Flammability:

This product is not flammable under normal condition of use. Maintain good ventilation. Do not smoke or work near ignition sources when using this product.

SAFE HANDLING INFORMATION

Storage and Transport:

Store in a cool dry place, out of direct sunlight. Not considered a Dangerous Good. No special transport precautions are necessary.

Incompatibilities:

Keep away from strong oxidising agents.

Hazardous Polymerisation:

Will not occur

Incompatibilities:

Will cure on contact with water or moisture. Oxidising materials

Spills and Disposal:

Immobilise using an absorbent and transfer to a suitable container for disposal. Wash walking surfaces with a detergent and water to reduce slipping hazard. Personnel should wear organic vapour mask during clean up. For disposal, consult responsible authority regarding statutory requirements

Fire/Explosion Hazard:

This product is not flammable. Fire fighters to wear self contained breathing apparatus if risk of exposure to vapours. Fire fighters to wear full protective equipment. Extinguish using water, water fog, carbon dioxide, dry chemical or foam.

Hazardous Decomposition:

Incomplete combustion can yield carbon oxides and traces of incomplete burned carbon compounds, silicon dioxide, nitrogen oxides, sulphur oxides, metal oxides, formaldehyde, quartz and other hazardous products of combustion.

MATERIAL SAFETY DATA SHEET FOR: EASY SEAL PAINT IT SILICONEReplaces: May 2001. Date of issue: May 2003

OTHER INFORMATION

No data

CONTACT POINT

Technical Manager (03) 9797 6222

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular, how to safely handle and use the product in the workplace. Since H.B. Fuller Company Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request.
