

# MOMAR

AUSTRALIA PTY LTD

Quality  
thru  
Research

A.C.N. 003 149 111

## Material Safety Data Sheet

QUICK IDENTIFIER (In Plant Common Name)

## DRAIN KLEAN

Momar Australia Pty Ltd  
Unit 1, 6 Turbo Road  
MARAYONG NSW 2148

Phone: 02 9831 4311  
Fax: 02 9831 2994  
Toll Free: 1800 267933

Contact: Mark Moskow

Date Prepared: 16<sup>th</sup> January 2003

U.N. Number: 1814

Class: 8 Corrosive

Hazchem: 2R

Packaging Group: 11

Poisons Schedule: S6

EPG: 8A2

HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA

### SECTION 1 - IDENTITY

Common Name: (used on label) DRAIN KLEAN

Chemical Name: Not applicable Chemical Family: Potassium hydroxide/dye blend

Formula: Aqueous mixture - liquid drain opener

### SECTION 2 - HAZARDOUS INGREDIENTS

Principal Hazardous Component(s)	CAS No.	% by Weight	Threshold limit value (units)
Potassium Hydroxide	1310-58-3	40 - 50	2mg/m <sup>3</sup> (ACGIH)

### SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

Boiling Point: 271°F Specific Gravity: (H<sub>2</sub>O=1) 1.450 Vapor Pressure: (mm Hg) 0.0038

Percent Volatile by Volume (%): 0 Vapor Density (Air = 1): 3.38 Evaporation Rate Not Applicable

Solubility in Water: Complete Reactivity in Water: None

Appearance and Odour : Red clear liquid with no odour.

Flash non-Flammable Limits Lower Upper Extinguisher as for Auto Ignition  
Point flammable In Air by Volume Not applicable Media surrounding fire Temperature N/A

Special Fire Fighting Procedures: Contact with water causes violent heat releasing action. Fire fighters wear self contained breathing apparatus with full face piece operated in pressure demand or other positive prssure mode and full protective clothing.

Unusual Fire and Explosion Hazards: Flammable hydrogen gas released on contact with aluminium, tin, zinc and their alloys.



