

# MOMAR

AUSTRALIA PTY LTD

Quality  
thru  
Research

A.C.N. 003 149 111

## Material Safety Data Sheet

QUICK IDENTIFIER (In Plant Common Name)

**QUICK DRAW (Aerosol)**

Momar Australia Pty Ltd  
Unit 1, 6 Turbo Road  
MARAYONG NSW 2148

Phone: 02 98314311  
Fax: 02 98312994  
Toll Free: 1800 267933

Contact: Mark Moskow

Date Prepared: 16<sup>th</sup> January 2003

U.N. Number: 1950

Class: 9 Substance

Hazchem: 2Y

Packaging Group: III

Poisons Schedule: S6

EPG: 2D1

**HAZARDOUS ACCORDING TO CRITERIA OF WORKSAFE AUSTRALIA**

### SECTION 1 - IDENTITY

Common Name: (used on label) **QUICK DRAW**

Chemical Name: Not applicable      Chemical Family: Lubricant Grease

Formula: Aerosol Lubricant Grease.

### SECTION 2 - HAZARDOUS INGREDIENTS

| Principal Hazardous Component(s) | CAS No.    | % by Weight | Threshold limit value (units) |
|----------------------------------|------------|-------------|-------------------------------|
| Aromatic Petroleum Distallates   | 64742-94-5 | 20-30       | Not Established               |
| Hexane                           | 110-54-3   | 35-45       | (ACGIH) 50 ppm                |
| Iso butan                        | 75-28-5    | 10          | (ACGIH)800 ppm                |
| Propane                          | 74-98-6    | 10          | (ACGIH)1000ppm                |

### SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS (Fire & Explosion Data)

|  |                              |  |
|--|------------------------------|--|
| Boiling Point:   | Specific Gravity:            | Vapor Pressure                               |
| N/A  | (H <sub>2</sub> O=1) .78     | (mm Hg) 46 psig                              |
| Percent Volatile   | Vapor Density                | Evaporation                                  |
| by Volume (%): 0   | Air = 1): Not est.           | Rate (ether =1) Slower                       |
| Solubility   | Reactivity                   |  |
| in Water: Negligible   | in Water: None               |  |
| Appearance and Odour : Red clear oily liquid-dries to grease-solvent odour   |                              |  |
| Flash  | Flammable Limits Lower Upper | Extinguisher CO <sub>2</sub> , Auto Ignition |
| Point flammable In Air by Volume   | N/A N/A                      | Media foam,dry chem Temperature Not est.     |
| Special Fire Fighting Procedures: Use water spray to keep fire exposed containers cool and to flush spills away from fire areas.Firefighters should wear self contained breathing apparatus. |                              |  |
| Unusual Fire and Explosion Hazards: Aerosol container pressurised with flammable propellant.   |                              |  |
| Do not expose to temperature above 1300F or container may explode.   |                              |  |



---

no hazard.

---