



Material Safety Data Sheet

Based on available information, not classified as hazardous according to criteria of NOHSC.
Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

1. Identification of the substance/preparation and of the company/undertaking

Product Name: BATHROOM & KITCHEN SEALANT

Packaging Type 75g tube
310g cartridge

Supplier: Selleys Pty Ltd
ABN: 67 000 049 427
Street Address: 1 Gow Street
Padstow 2211
Australia

Telephone Number: +61 2 9781 8777
Facsimile: +61 2 9781 8825

Emergency Telephone: 1 800 033 111 (ALL HOURS)

2. Composition/information on ingredients

Product Description: Silicone sealant for use around baths, showers and sinks. White paste with a strong acetic acid odour.

Polydimethyl siloxane 63148-62-9	>60%	-
Fillers and plasticisers	10-<30%	-
Methyltriacetoxysilane 4253-34-3	1-<10%	-
Additives	to 100%	-

3. Hazards identification

Poisons Schedule: None allocated.

4. First-aid measures

For advice, contact a Poisons Information Centre (Phone eg. Australia 131 126; New Zealand 0 800 764766) or a doctor.

Inhalation: Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

Skin Contact: Wipe excess material from skin with a clean rag or paper towel (do NOT use solvent to clean skin).

Product Name: BATHROOM & KITCHEN SEALANT
Substance No: 000703514201

Issued: 02/12/2002

Version: 2



Material Safety Data Sheet

Eye Contact: Remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.
If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

Ingestion: Rinse mouth with water. If swallowed, give a glass of water to drink. If vomiting occurs give further water. Seek medical assistance.

Notes to physician: Treat symptomatically.

5. Fire-fighting measures

Specific Hazards: Combustible paste.

Fire-fighting advice: Combustible but under normal conditions of use is not considered a risk. On burning will emit toxic fumes, including those of acetic acid and oxides of carbon. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Suitable Extinguishing Media: Water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. Accidental release measures

SMALL SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wipe up with rag or absorbent paper. Any residual material can be cleaned up with mineral turpentine or similar hydrocarbon solvent, or acetone based nail polish remover. Cured material can be removed by cutting or abrasion.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Scrape up excess material before cure. Collect and seal in properly labelled containers or drums for disposal. Cured material can only be removed by cutting or abrasion.

7. Handling and storage

Handling advice: Avoid skin and eye contact and breathing in vapour.

Storage advice: Store in a cool, dry, well ventilated place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

8. Exposure controls/personal protection

Occupational Exposure Limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for substance liberated during application and cure:

Acetic acid: 8hr TWA = 25 mg/m³ (10 ppm), 15 min STEL = 37 mg/m³ (15 ppm)

As published by the National Occupational Health and Safety Commission.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week

Product Name: BATHROOM & KITCHEN SEALANT
Substance No: 000703514201

Issued: 02/12/2002

Version: 2



Material Safety Data Sheet

over an entire working life.

STEL (Short Term Exposure Limit) – the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health or, not cause undue discomfort to, nearly all workers.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering Control Measures:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Use in well ventilated areas. Keep containers closed when not in use.

Personal Protective Equipment:

Selleys Safe Handling Code: Green

Green - Wear clean overalls, safety boots, general purpose gloves (PVC) and safety spectacles. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been removed from fingertips, nails and cuticles. If risk of inhalation exists, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet.

9. Physical and chemical properties

Physical state:	Paste
Colour:	White
Odour:	Acetic acid
Solubility:	Insoluble in water. Uncured material is soluble in organic solvents. No solvent known for cured sealant.
Specific Gravity:	1.05 @ 20°C
Relative Vapour Density (air=1):	N Av
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	N Av
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
% Volatile by Volume:	<8
Solubility in water (g/L):	Insoluble
Melting Point/Range (°C):	N App
Boiling Point/Range (°C):	N Av
Decomposition Point (°C):	N Av
Sublimation Point (°C):	N App
pH:	N App
Viscosity:	N Av
Evaporation Rate:	N Av

10. Stability and reactivity

Stability: Incompatible with oxidising agents .

11. Toxicological information

Product Name: BATHROOM & KITCHEN SEALANT
Substance No: 000703514201

Issued: 02/12/2002

Version: 2



Material Safety Data Sheet

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion: Swallowing may result in irritation to the mouth and throat. No adverse effects expected after swallowing cured (solvent free) sealant.
Eye contact: May be an eye irritant.
Skin contact: Contact with skin may result in irritation. Cured sealant (solvent free) is not expected to be a skin irritant.
Inhalation: Acetic acid is liberated during application and setting. Breathing in vapour may produce respiratory irritation.

Long Term Effects:
No information available for the product.

Toxicological Data:
No LD50 data available for the product.

12. Ecotoxicological information

Avoid contaminating waterways.

13. Disposal considerations

Refer to Waste Management Authority. Normally suitable for disposal at approved land waste site.

14. Transport information

Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

15. Regulatory information

Classification: Based on available information, not classified as hazardous according to criteria of NOHSC.
Poisons Schedule: None allocated.

Product Name: BATHROOM & KITCHEN SEALANT
Substance No: 000703514201

Issued: 02/12/2002 **Version:** 2



Material Safety Data Sheet

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. Other information

This material safety data sheet has been prepared by SH&E Shared Services, Orica.

For further copies of this sheet or other product information contact Selley's Proprietary Limited Customer Service.

Phone: 1300 555 205 (Australia wide)

Fax: 1300 555 305 (Australia wide)

Phone: 9 820 4852 (New Zealand)

Fax: 0800 804 583 (New Zealand)

Reason(s) for Issue:

5 Yearly Revised Primary MSDS

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Orica Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Orica representative or Orica Limited at the contact details on page 1.

Orica Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: BATHROOM & KITCHEN SEALANT
Substance No: 000703514201

Issued: 02/12/2002

Version: 2