



Material Safety Data Sheet

This material is hazardous according to criteria of NOHSC.

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail.

1. Identification of the substance/preparation and of the company/undertaking

Product Name: EZY GLIDE (AEROSOL)

Supplier: Selleys Pty Ltd
ABN: 67 000 049 427
Street Address: 1 Gow Street
Padstow 2211
Australia
Telephone Number: +61 2 9781 8777
Facsimile: +61 2 9781 8825

Emergency Telephone: 1 800 033 111 (ALL HOURS)

2. Composition/information on ingredients

Product Description: Lubricant for windows, drawers, zippers, sliding doors and locks. Product sprays as a clear liquid with a hydrocarbon odour.

Components / CAS Number	Proportion	Risk Phrases
Butane 106-97-8	10-<30%	R12
Propane 74-98-6	10-<30%	R12
Naphtha (petroleum), hydrotreated light 64742-49-0	30-60%	R11, R51/53, R65
Ingredients determined not to be hazardous	<1%	-
-		

3. Hazards identification

Risk Phrases: Extremely Flammable. Harmful: May cause lung damage if swallowed.

Poisons Schedule: None allocated.

4. First-aid measures

Product Name: EZY GLIDE (AEROSOL)
Substance No: 000703530701

Issued: 30/06/2004
Version: 2

Page 1 of 6



Material Safety Data Sheet

For advice, contact a Poisons Information Centre (Phone eg. Australia 131 126; New Zealand 0 800 764766) or a doctor.

- Inhalation:** Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discoloration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.
- Skin Contact:** If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.
- Eye Contact:** If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.
- Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.
- Notes to physician:** Treat symptomatically.

5. Fire-fighting measures

- Specific Hazards:** Flammable gas. May form flammable vapour mixtures with air. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Vapour may travel a considerable distance to source of ignition and flash back.
- Fire-fighting advice:** On burning will emit toxic fumes. Heating can cause expansion or decomposition of the material, which can lead to the containers exploding. If safe to do so, remove containers from the path of fire. Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.
- Suitable Extinguishing Media:** Water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. Accidental release measures

Shut off all possible sources of ignition. In the event of an aerosol can developing a leak, allow to fully discharge in the open air before disposal.

7. Handling and storage

- Handling advice:** Avoid skin and eye contact and breathing in vapour, mists and aerosols. Ensure spray nozzle is always directed away from the user.
- Storage advice:** Store in cool place and out of direct sunlight. Store away from sources of heat or ignition. Store away from oxidising agents. Keep containers closed when not in use - check regularly for leaks.

Product Name: EZY GLIDE (AEROSOL)
Substance No: 000703530701

Issued: 30/06/2004

Version: 2



Material Safety Data Sheet

8. Exposure controls/personal protection

Occupational Exposure Limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

Butane: 8hr TWA = 1900 mg/m³ (800 ppm)

Propane: Asphyxiant

As published by the National Occupational Health and Safety Commission.

No Exposure Standards assigned to other constituents.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

Asphyxiant – gases which can lead to reduction of oxygen concentration by displacement or dilution. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

Engineering Control Measures:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Exposure Standards. Use in well ventilated areas. Keep containers closed when not in use. An asphyxiant gas which can lead to the displacement or dilution of oxygen. The minimum oxygen content in air should be 18% by volume under normal atmospheric pressure.

Personal Protective Equipment:

Selleys Safe Handling Code: Green

Green - Wear clean overalls, safety boots, general purpose gloves (PVC) and safety spectacles. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

For leaking aerosol cans: Blue - Wear clean overalls, safety boots, general purpose gloves (PVC) and full face visor. If risk of inhalation exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. Physical and chemical properties

Physical state:	Aerosol
Odour:	Hydrocarbon
Solubility:	Insoluble in water.
Specific Gravity:	0.61 @20°C

Product Name: **EZY GLIDE (AEROSOL)**
Substance No: **000703530701**

Issued: **30/06/2004**

Version: **2**



Material Safety Data Sheet

Relative Vapour Density (air=1):	N Av
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	-104 (propane)
Flammability Limits (%):	2.4-9.5 (propane)
Autoignition Temperature (°C):	N Av
% Volatile by Volume:	99
Melting Point/Range (°C):	N App
Boiling Point/Range (°C):	N Av
Decomposition Point (°C):	N Av
pH:	N App
Viscosity:	N App
Evaporation Rate:	N Av

10. Stability and reactivity

Stability: Incompatible with oxidising agents .

11. Toxicological information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

- Ingestion:** Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs.
- Eye contact:** May be an eye irritant.
- Skin contact:** Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.
- Inhalation:** Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness. Intentional misuse by deliberately concentrating and breathing the contents can be harmful or fatal.

Long Term Effects:
No information available for the product.

Toxicological Data:
No LD50 data available for the product.

12. Ecotoxicological information

Avoid contaminating waterways.

Product Name: EZY GLIDE (AEROSOL)
Substance No: 000703530701

Issued: 30/06/2004 **Version:** 2
Page 4 of 6



Material Safety Data Sheet

13. Disposal considerations

Refer to Waste Management Authority. Advise flammable nature. Do not puncture or burn can when empty; contents are under pressure. If aerosol can develops a leak, allow to fully discharge before disposal. Normally suitable for disposal at approved land waste site.

14. Transport information

Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail.

UN No: 1950
Class-primary: 2.1 Flammable Gas
Proper Shipping Name: AEROSOLS

Hazchem Code: 2Y

Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1950
Class-primary: 2.1 Flammable Gas
Proper Shipping Name: AEROSOLS

Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 1950
Class-primary: 2.1 Flammable Gas
Proper Shipping Name: AEROSOLS, FLAMMABLE

15. Regulatory information

Classification: This material is hazardous according to criteria of NOHSC.
Xn: Harmful

Risk Phrase(s): R12: Extremely Flammable.
R65: Harmful: May cause lung damage if swallowed.

Product Name: EZY GLIDE (AEROSOL)
Substance No: 000703530701

Issued: 30/06/2004

Version: 2



Material Safety Data Sheet

Safety Phrase(s): S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Poisons Schedule: None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

16. Other information

This material safety data sheet has been prepared by SH&E Shared Services, Orica.
For further copies of this sheet or other product information contact Selley's Proprietary Limited Customer Service.
Phone: 1300 555 205 (Australia wide)
Fax: 1300 555 305 (Australia wide)
Phone: 9 820 4852 (New Zealand)
Fax: 0800 804 583 (New Zealand)

Reason(s) for Issue:

5 Yearly Revised Primary MSDS

This MSDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Orica Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their Orica representative or Orica Limited at the contact details on page 1.

Orica Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.

Product Name: EZY GLIDE (AEROSOL)
Substance No: 000703530701

Issued: 30/06/2004

Version: 2