

# Safety Data Sheet

LOCTITE 567 THREAD SEALANT

Page 1 of 9

SDS No.: 153487 V001.4 Date of issue: 08.05.2020

Section 1. Identification of the substance/preparation and of the company/undertaking		
Product name:	LOCTITE 567 THREAD SEALANT	
Intended use:	Adhesive	
Supplier: Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia		
Phone: +61 (3) 9724 644	14	
Emergency information:	24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379	

## Section 2. Hazards identification

Classification of the substance or mixture Hazardous according to the criteria of Safe Work Australia.

#### **GHS Classification:**

Hazard Class	Hazard Category
Skin sensitizer	Category 1
Eye irritation	Category 2
Acute hazards to the aquatic	Category 3
environment	
Hazard pictogram:	<u>(!</u> )
Signal word:	None

Hazard statement(s):	H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H402 Harmful to aquatic life.
Precautionary Statement(s):	
Prevention:	P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
	P272 Contaminated work clothing should not be allowed out of the workplace.
	P264 Wash affected area thoroughly after handling.
	P280 Wear protective gloves, eye protection, and face protection.
	P273 Avoid release to the environment.
Response:	P302+P352 IF ON SKIN: Wash with plenty of soap and water.
	P363 Wash contaminated clothing before reuse.
	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+P313 If eye irritation persists: Get medical advice/attention.
Disposal:	P501 Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations.

#### **Dangerous Goods information:**

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

# Signal word:

HĂZARDOUS

## Section 3. Composition / information on ingredients

General	chemical	description:
Type of	preparati	on:

Mixture Anaerobic Sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Titanium dioxide	13463-67-7	< 10 %
Silica, amorphous, fumed, crystal-free	112945-52-5	< 10 %
reaction product: bisphenol-A-(epichlorhydrin)	25068-38-6	< 1%
non hazardous ingredients~		<= 70 %

Section 4. First aid measures		
Ingestion:	Do not induce vomiting. Have victim rinse mouth thoroughly with water. Seek medical advice.	
Skin:	Rinse with running water and soap. Remove contaminated clothing and footwear. Seek medical advice.	
Eyes:	Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.	
Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.	
First Aid facilities:	Eye wash Normal washroom facilities	

Medical attention and special treatment:

Treat symptomatically and supportively.

Section 5. Fire fighting measures		
Suitable extinguishing media:	Carbon dioxide, foam, powder	
Decomposition products in case of fire:	Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide. Carbon dioxide.	
Special protective equipment for fire-fighters:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.	

Section 6. Accidental release measures		
Personal precautions:	Avoid skin and eye contact. Ensure adequate ventilation.	
	Wear appropriate personal protective equipment.	
Environmental precautions:	Do not let product enter drains.	
Clean-up methods:	For small spills wipe up with paper towel and place in container for disposal. For large spills absorb onto inert absorbent material and place in sealed container for disposal.	

	Section 7. Handling and storage		
Precautions for safe handling:	Use only in well-ventilated areas. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling.		
Conditions for safe storage:	Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.		

## Section 8. Exposure controls / personal protection

### National exposure standards:

Ingredient [Regulated substance]	form of exposure	TWA (ppm)	TWA (mg/m3)	Peak Limit. (ppm)	Peak Limit. (mg/m3)	STEL (ppm)	STEL (mg/m3)
TITANIUM DIOXIDE 13463-67-7	Inhalable dust.		10				
SILICA, AMORPHOUS: FUMED SILICA (RESPIRABLE DUST) 112945-52-5	Respirable dust.		2				
FUMED SILICA (RESPIRABLE DUST) 112945-52-5	Respirable dust.		2				

LOCTITE 567 THREAD SEALANT

Engineering controls:	Ensure good ventilation/suction at the workplace.
Eye protection:	Safety goggles or safety glasses with side shields.
Skin protection:	Use impermeable gloves and protective clothing as necessary to prevent skin contact.
	Neoprene gloves.
	Butyl rubber gloves.
	Natural rubber gloves.
Respiratory protection:	If inhalation risk exists, wear a respirator or air supplied mask complying with the requirements of AS/NZS 1715 and AS/NZS 1716.

	Section 9. Physical and chemical properties
Specific gravity:	1.14
Boiling point:	> 149 °C (> 300.2 °F)
Flash point:	> 93.3 °C (> 199.94 °F)
<b>Vapor pressure:</b> (; 27 °C (80.6 °F))	< 27 mbar
Density:	1.14 g/cm3
VOC content:	0.13 % 1.38 g/l
Stability:	Stable under recommended storage conditions.
Conditions to avoid:	Excessive heat.
Incompatible materials:	Reacts with strong oxidants.
Hazardous decomposition	Thermal decomposition can lead to release of irritating gases and vapors.
products:	Carbon monoxide. Carbon dioxide.

# Section 11. Toxicological information

Health Effects:	
Ingestion:	Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Skin:	May cause skin irritation.
	Symptoms may include redness, edema, drying, defatting and cracking of the skin.
	May cause skin sensitization.
Eyes:	May cause mild irritation
	Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
Inhalation:	Inhalation of mists/vapors of this product may cause dizziness, nausea, and respiratory tract congestion.

### Acute toxicity:

Hazardous components CAS-No.	Value type	Value	Route of application	Exposure time	Species	Method
Titanium dioxide 13463-67-7	LD50 LC50 LD50	> 5,000 mg/kg > 6.82 mg/l >= 10,000 mg/kg	oral inhalation dermal	4 h	rat rat hamster	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure) not specified not specified
Silica, amorphous, fumed, crystal-free 112945-52-5	LD50 LC50 LD50	> 5,000 mg/kg > 58.8 mg/l > 2,000 mg/kg	oral inhalation dermal	4 h	rat rat rabbit	OECD Guideline 401 (Acute Oral Toxicity) OECD Guideline 403 (Acute Inhalation Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	LD50 LD50	> 2,000 mg/kg > 2,000 mg/kg	oral dermal		rat rat	OECD Guideline 420 (Acute Oral Toxicity) OECD Guideline 402 (Acute Dermal Toxicity)

### Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Silica, amorphous, fumed, crystal-free 112945-52-5	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	moderately irritating	24 h	rabbit	Draize Test

### Serious eye damage/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Silica, amorphous, fumed, crystal-free 112945-52-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

### Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Titanium dioxide 13463-67-7	not sensitising	Mouse local lymphnod e assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

### Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Titanium dioxide 13463-67-7	negative negative negative	bacterial reverse mutation assay (e.g Ames test) in vitro mammalian chromosome aberration test mammalian cell gene mutation assay	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide 13463-67-7	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Silica, amorphous, fumed, crystal-free 112945-52-5	negative negative negative	bacterial reverse mutation assay (e.g Ames test) mammalian cell gene mutation assay in vitro mammalian chromosome aberration test	with and without with and without with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay) OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test) OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	negative	oral: gavage		mouse	not specified

### Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Titanium dioxide 13463-67-7	NOAEL=1,000 mg/kg	oral: gavage	90 ddaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Silica, amorphous, fumed, crystal-free 112945-52-5	NOAEL=< 0.046 mg/l	inhalation	14 days6 hours/day, 5 days/week	rat	not specified
Silica, amorphous, fumed, crystal-free 112945-52-5	NOAEL=> 4,500 mg/kg	oral: feed	13 weeksdaily, continous	rat	
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	NOAEL=50 mg/kg	oral: gavage	14 wdaily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

#### General ecological information:

Cured Loctite products are typical polymers and do not pose any immediate environmental hazards., Do not empty into drains / surface water / ground water.

### Toxicity:

Value	Value	Acute	Exposure	Species	Method
type		Study	time		
LC50	> 10,000 mg/l	Fish	96 h	Brachydanio rerio (new name:	OECD Guideline
	-			Danio rerio)	203 (Fish, Acute
					Toxicity Test)
EL50	> 1,000 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline
					202 (Daphnia sp.
					Acute
					Immobilisation
					Test)
NOELR	10,000 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline
					201 (Alga, Growth
					Inhibition Test)
EL50	> 10,000 mg/l	Algae	72 h	Desmodesmus subspicatus	OECD Guideline
					201 (Alga, Growth
	10.000 #				Inhibition Test)
EC0	10,000 mg/l	Bacteria	30 min	Pseudomonas putida	DIN 38412, part 27
					(Bacterial oxygen
LCEO	1.75	E.1	0(1		consumption test)
LC30	1./5 mg/1	Fish	96 h	Oncornynchus mykiss	OECD Guideline
					203 (Fish, Acute
EC50	1.7 ma/l	Donhnia	19 1	Danhnia magna	Toxicity Test) OECD Guideline
EC30	1./ mg/1	Daphnia	48 h	Dapinia magna	202 (Daphnia sp.
					Acute
					Immobilisation
					Test)
EC50	> 11  mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline
LCJU	× 11 mg/1	Ingae	/2 11	Sechedesinds capiteonidam	201 (Alga, Growth
					Inhibition Test)
NOEC	4.2 mg/l	Algae	72 h	Scenedesmus capricornutum	OECD Guideline
HOLE	1.2 mg/1	riigue	/211	Sechedesinds cupreofination	201 (Alga, Growth
					Inhibition Test)
IC50	> 100 mg/l	Bacteria	3 h	activated sludge, industrial	other guideline:
	type LC50 EL50 NOELR EL50 EC0 LC50 EC50 EC50 NOEC	type           LC50         > 10,000 mg/l           EL50         > 1,000 mg/l           NOELR         10,000 mg/l           EL50         > 10,000 mg/l           EL50         > 10,000 mg/l           EC50         10,000 mg/l           EC0         10,000 mg/l           EC50         1.75 mg/l           EC50         > 11 mg/l           NOEC         4.2 mg/l	type         Toxicity Study           LC50         > 10,000 mg/l         Fish           EL50         > 1,000 mg/l         Daphnia           NOELR         10,000 mg/l         Algae           EL50         > 10,000 mg/l         Algae           EL50         > 10,000 mg/l         Algae           EL50         > 10,000 mg/l         Bacteria           LC50         1.75 mg/l         Fish           EC50         1.7 mg/l         Daphnia           EC50         > 11 mg/l         Algae           NOEC         4.2 mg/l         Algae	type         Toxicity Study         time time           LC50         > 10,000 mg/l         Fish         96 h           EL50         > 1,000 mg/l         Daphnia         24 h           NOELR         10,000 mg/l         Algae         72 h           EL50         > 10,000 mg/l         Algae         72 h           EL50         > 10,000 mg/l         Algae         72 h           EL50         > 10,000 mg/l         Bacteria         30 min           LC50         1.75 mg/l         Fish         96 h           EC50         1.7 mg/l         Daphnia         48 h           EC50         > 11 mg/l         Algae         72 h           NOEC         4.2 mg/l         Algae         72 h	typeToxicity StudytimeTown timeLC50>10,000 mg/lFish96 hBrachydanio rerio (new name: Danio rerio)EL50>1,000 mg/lDaphnia24 hDaphnia magnaNOELR10,000 mg/lAlgae72 hDesmodesmus subspicatusEL50>10,000 mg/lAlgae72 hDesmodesmus subspicatusEL50>10,000 mg/lAlgae72 hDesmodesmus subspicatusEC010,000 mg/lBacteria30 minPseudomonas putidaLC501.75 mg/lFish96 hOncorhynchus mykissEC501.7 mg/lDaphnia48 hDaphnia magnaNOEC4.2 mg/lAlgae72 hScenedesmus capricornutum

### Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
reaction product: bisphenol-A-	not readily biodegradable.	aerobic	5 %	OECD Guideline 301 F (Ready
(epichlorhydrin)				Biodegradability: Manometric
25068-38-6				Respirometry Test)

#### Bioaccumulative potential / Mobility in soil:

Hazardous components CAS-No.	LogPow	Bioconcentration factor (BCF)	Exposure time	Species	Temperature	Method
Silica, amorphous, fumed, crystal-free 112945-52-5	0.53					QSAR (Quantitative Structure Activity Relationship)
reaction product: bisphenol-A- (epichlorhydrin) 25068-38-6	3.242				25 °C	EU Method A.8 (Partition Coefficient)

## Section 13. Disposal considerations

Waste disposal of product:

Dispose of in accordance with local and national regulations.

### Section 14. Transport information

#### **Road and Rail Transport:**

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

#### Marine transport IMDG:

Not dangerous goods

#### Air transport IATA: Not dangerous goods

## Section 15. Regulatory information

None

SUSMP Poisons Schedule

### Section 16. Other information

Abbreviations/acronyms:	<ul> <li>ADGC - Australian Dangerous Goods Code</li> <li>GHS: Globally Harmonized System</li> <li>CAS: Chemical Abstracts Service</li> <li>TWA - Time weighted average</li> <li>STEL - Short term exposure limit</li> <li>LD 50: Lethal Dose 50%</li> <li>OECD: Organization for Economic Cooperation and Development</li> <li>LC 50: Lethal Concentration 50%</li> <li>IMDG: International Maritime Dangerous Goods code</li> <li>IATA DCB: Lethermiter A Americation Processing Conder Reputations</li> </ul>
	IATA-DGR: International Air Transport Association – Dangerous Goods Regulations
Reason for issue:	Reviewed SDS. Reissued with new date. involved chapters: 1,2,3,8,15,16

Date of previous issue:	11.05.2015
Disclaimer:	
	The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.
	The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.
	This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.
	No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.