

Safety Data Sheet

LOCTITE 569 HYDRAULIC SEALANT

Page 1 of 6

SDS No.: 150775

V001.4 Date of issue: 07.02.2020

respiratory tract irritation

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE 569 HYDRAULIC SEALANT

Intended use: Anaerobic thread Sealant

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137

Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

<u>Hazard Class</u> <u>Hazard Category</u> <u>Target organ</u>

Serious eye irritation Category 2A
Target Organ Systemic Toxicant - Category 3

Single exposure

Acute hazards to the aquatic category 3 environment Chronic hazards to the aquatic category 3 environment

Hazard pictogram:

Signal word: Warning

SDS No.: 150775 V001.4

LOCTITE 569 HYDRAULIC SEALANT

Hazard statement(s): H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment. P280 Wear eye protection/face protection.

Response: P304+P340+P312 IF INHALED: Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Signal word:

HAZARDOUS

Section 3. Composition / information on ingredients

General chemical description: Mixture

Type of preparation: Anaerobic Sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
α, α-dimethylbenzyl hydroperoxide	80-15-9	1-< 3 %

Section 4. First aid measures

Ingestion: Rinse mouth, do not induce vomiting, consult a doctor.

Skin: Rinse with running water and soap.

Remove contaminated clothing and footwear. If skin irritation persists, call a physician.

Eyes: Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if

necessary.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash

Normal washroom facilities

Medical attention and special

treatment:

Treat symptomatically.

Page 3 of 6

SDS No.: 150775 V001.4

LOCTITE 569 HYDRAULIC SEALANT

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Decomposition products in case of Oxides of carbon.

Irritating fumes.

Particular danger in case of fire: See section 10.

Special protective equipment for

fire-fighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Section 6. Accidental release measures

Personal precautions: Avoid skin and eye contact.

Ensure adequate ventilation.

People who are not part of the emergency service should stay away.

Environmental precautions: Do not let product enter drains.

Follow all local, state, federal and provincial regulations for disposal.

For small spills wipe up with paper towel and place in container for disposal. Clean-up methods:

For large spills absorb onto inert absorbent material and place in sealed container for

disposal.

Section 7. Handling and storage

Precautions for safe handling: Use only in well-ventilated areas.

Conditions for safe storage: Store in original containers at 8-21°C (46.4-69.8°F) and do not return residual materials to

containers as contamination may reduce the shelf life of the bulk product.

Section 8. Exposure controls / personal protection

National exposure standards:

None

Engineering controls: Ensure good ventilation/suction at the workplace.

Eye protection: Safety goggles or safety glasses with side shields.

Use impermeable gloves and protective clothing as necessary to prevent skin contact. Skin protection:

Neoprene gloves.

Butyl rubber gloves.

Natural rubber gloves.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

LOCTITE 569 HYDRAULIC SEALANT

Appearance: brown liquid Odor: mild

Specific gravity: 1.049 **Flash point:** > 93.3 °C (> 199.94 °F)

(Tagliabue closed cup)

Solubility in water: < 1.00000 g/l

Section 10. Stability and reactivity

Conditions to avoid: Excessive heat.

Incompatible materials: Reacts with strong oxidants.

Hazardous decomposition

products:

Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be

generated by thermal decomposition or combustion.

Section 11. Toxicological information

Health Effects:

Ingestion: Ingestion may cause stomach ache and vomiting.

Skin: May cause skin irritation.

Eyes: Contact with eyes will cause irritation.

Inhalation: This product is irritating to the respiratory system.

Aggravated med.

condition:

Eye, skin, and respiratory disorders.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
α, α-dimethylbenzyl	LD50	382 mg/kg	oral		rat	other guideline:
hydroperoxide	LD50	530 - 1,060			rat	other guideline:
80-15-9	Acute	mg/kg	dermal			Expert judgement
	toxicity	1,100 mg/kg	dermal			
	estimate					
	(ATE)					

Skin corrosion/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
α, α-dimethylbenzyl	corrosive		rabbit	Draize Test
hydroperoxide				
80-15-9				

Germ cell mutagenicity:

Hazardous components CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
α, α-dimethylbenzyl hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
α, α-dimethylbenzyl hydroperoxide 80-15-9	negative	dermal		mouse	not specified

LOCTITE 569 HYDRAULIC SEALANT

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
α, α-dimethylbenzyl		inhalation:	6 h/d5 d/w	rat	not specified
hydroperoxide		aerosol			
80-15-9					

Section 12. Ecological information

General ecological information: Cured Loctite products are typical polymers and do not pose any immediate

environmental hazards., Do not empty into drains / surface water / ground water.

Ecotoxicity: Do not empty into drains / surface water / ground water.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
α, α-dimethylbenzyl hydroperoxide 80-15-9	LC50	3.9 mg/l	Fish	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC50	18 mg/l	Daphnia	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	ErC50	3.1 mg/l	Algae	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	EC10	70 mg/l	Bacteria	30 min		not specified

Persistence and degradability:

Hazardous components CAS-No.	Result	Route of application	Degradability	Method
α, α-dimethylbenzyl hydroperoxide 80-15-9		no data	0 %	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)

Bioaccumulative potential / Mobility in soil:

Hazardous components	LogPow	Bioconcentration	Exposure	Species	Temperature	Method
CAS-No.		factor (BCF)	time			
α, α-dimethylbenzyl hydroperoxide 80-15-9		9.1		calculation		OECD Guideline 305 (Bioconcentration: Flow- through Fish Test)
α, α-dimethylbenzyl hydroperoxide 80-15-9	2.16					not specified

Section 13. Disposal considerations

Waste disposal of product: Dispose of in accordance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

SDS No.: 150775 V001.4

LOCTITE 569 HYDRAULIC SEALANT

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

SUSMP Poisons Schedule

None

Section 16. Other information

Abbreviations/acronyms: IATA-DGR: International Air Transport Association – Dangerous Goods Regulations

GHS: Globally Harmonized System CAS: Chemical Abstracts Service LD 50: Lethal Dose 50%

OECD: Organization for Economic Cooperation and Development

ADGC - Australian Dangerous Goods Code

IMDG: International Maritime Dangerous Goods code

Reason for issue: Reviewed MSDS. Reissued with new date. involved chapters: 1,2,3

Date of previous issue: 04.02.2015

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material.

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.